

Statement of Basis of the Federal Operating Permit

Eastman Chemical Company

Site/Area Name: C7 - Materials Handling
Physical location: 300 Kodak Blvd
Nearest City: Longview
County: Harrison

Permit Number: O1436
Project Type: Renewal

Standard Industrial Classification (SIC) Code: 2869
SIC Name: Industrial Organic Chemicals

This Statement of Basis sets forth the legal and factual basis for the draft permit conditions in accordance with 30 TAC §122.201(a)(4). Per 30 TAC §§ 122.241 and 243, the permit holder has submitted an application under § 122.134 for permit renewal. This document may include the following information:

- A description of the facility/area process description;
- A basis for applying permit shields;
- A list of the federal regulatory applicability determinations;
- A table listing the determination of applicable requirements;
- A list of the New Source Review Requirements;
- The rationale for periodic monitoring methods selected;
- The rationale for compliance assurance methods selected;
- A compliance status; and
- A list of available unit attribute forms.

Prepared on: March 16, 2015

Operating Permit Basis of Determination

Permit Area Process Description

The 'C-7 - Materials Handling' application area includes the Raw Materials and Product Distribution system and the Railcar Washing Facility.

The Raw Materials and Product Distribution system is used to unload materials and feedstock from railcars and trucks into storage tanks and then distribute them to the Texas Operations process units; and to load Texas Operation products into railcars and trucks for shipment. Additionally, products are received by rail from other Eastman Chemical Company divisions, stored, and later reloaded into railcars and trucks for reshipment. All these operations are performed on an as needed basis. Major process steps are railcar unloading, product storage, and railcar and truck loading. Emissions are from storage tanks and loading racks, as well as fugitive equipment leaks. The major pollutants are Volatile Organic Carbon (VOC) and Hazardous Air Pollutants (HAP).

The Railcar Washing Facility is used on an intermittent basis. Process steps are draining and washing of railcars and loading of wastes into vacuum trucks for disposal. Emissions are from storage tanks and loading racks, as well as fugitive equipment leaks and wastewater.

FOPs at Site

The "application area" consists of the emission units and that portion of the site included in the application and this permit. Multiple FOPs may be issued to a site in accordance with 30 TAC § 122.201(e). When there is only one area for the site, then the application information and permit will include all units at the site. Additional FOPs that exist at the site, if any, are listed below.

Additional FOPs: O1968, O1970, O1971, O1972, O1973, O1974, O1975, O1976, O1977, O1978, O1979, O1981, O1982

Major Source Pollutants

The table below specifies the pollutants for which the site is a major source:

Major Pollutants	VOC, SO ₂ , PM, NO _x , HAPS, CO
------------------	---

Reading State of Texas's Federal Operating Permit

The Title V Federal Operating Permit (FOP) lists all state and federal air emission regulations and New Source Review (NSR) authorizations (collectively known as "applicable requirements") that apply at a particular site or permit area (in the event a site has multiple FOPs). **The FOP does not authorize new emissions or new construction activities.** The FOP begins with an introductory page which is common to all Title V permits. This page gives the details of the company, states the authority of the issuing agency, requires the company to operate in accordance with this permit and 30 Texas Administrative Code (TAC) Chapter 122, requires adherence with NSR requirements of 30 TAC Chapter 116, and finally indicates the permit number and the issuance date.

This is followed by the table of contents, which is generally composed of the following elements. Not all permits will have all of the elements.

- General Terms and Conditions
- Special Terms and Conditions
 - Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting

- Additional Monitoring Requirements
- New Source Review Authorization Requirements
- Compliance Requirements
- Protection of Stratosphere Ozone
- Permit Location
- Permit Shield (30 TAC § 122.148)
- Attachments
 - Applicable Requirements Summary
 - Unit Summary
 - Applicable Requirements Summary
 - Additional Monitoring Requirements
 - Permit Shield
 - New Source Review Authorization References
 - Compliance Plan
 - Alternative Requirements
- Appendix A
 - Acronym list
- Appendix B
 - Copies of major NSR authorizations

General Terms and Conditions

The General Terms and Conditions are the same and appear in all permits. The first paragraph lists the specific citations for 30 TAC Chapter 122 requirements that apply to all Title V permit holders. The second paragraph describes the requirements for record retention. The third paragraph provides details for voiding the permit, if applicable. The fourth paragraph states that the permit holder shall comply with the requirements of 30 TAC Chapter 116 by obtaining a New Source Review authorization prior to new construction or modification of emission units located in the area covered by this permit. The fifth paragraph provides details on submission of reports required by the permit.

Special Terms and Conditions

Emissions Limitations and Standards, Monitoring and Testing, and Recordkeeping and Reporting. The TCEQ has designated certain applicable requirements as site-wide requirements. A site-wide requirement is a requirement that applies uniformly to all the units or activities at the site. Units with only site-wide requirements are addressed on Form OP-REQ1 and are not required to be listed separately on a OP-UA Form or Form OP-SUM. Form OP-SUM must list all units addressed in the application and provide identifying information, applicable OP-UA Forms, and preconstruction authorizations. The various OP-UA Forms provide the characteristics of each unit from which applicable requirements are established. Some exceptions exist as a few units may have both site-wide requirements and unit specific requirements.

Other conditions. The other entries under special terms and conditions are in general terms referring to compliance with the more detailed data listed in the attachments.

Attachments

Applicable Requirements Summary. The first attachment, the Applicable Requirements Summary, has two tables, addressing unit specific requirements. The first table, the Unit Summary, includes a list of units with applicable requirements, the unit type, the applicable regulation, and the requirement driver. The intent of the requirement driver is to inform the reader that a given unit may have several different operating scenarios and the differences between those operating scenarios.

The applicable requirements summary table provides the detailed citations of the rules that apply to the various units. For each unit and operating scenario, there is an added modifier called the “index number,” detailed citations specifying monitoring and testing requirements, recordkeeping requirements, and reporting requirements. The data for this table are based on data supplied by the applicant on the OP-SUM and various OP-UA forms.

Additional Monitoring Requirement. The next attachment includes additional monitoring the applicant must perform to ensure compliance with the applicable standard. Compliance assurance monitoring (CAM) is often required to provide a reasonable assurance of compliance with applicable emission limitations/standards for large emission units that use control devices to achieve compliance with applicant requirements. When necessary, periodic monitoring (PM) requirements are specified for certain parameters (i.e. feed rates, flow rates, temperature, fuel type and consumption, etc.) to determine if a term and condition or emission unit is operating within specified limits to control emissions. These additional monitoring approaches may be required for two reasons. First, the applicable rules do not adequately specify monitoring requirements (exception- Maximum Achievable Control Technology Standards (MACTs) generally have sufficient monitoring), and second, monitoring may be required to fill gaps in the monitoring requirements of certain applicable requirements. In situations where the NSR permit is the applicable requirement requiring extra monitoring for a specific emission unit, the preferred solution is to have the monitoring requirements in the NSR permit updated so that all NSR requirements are consolidated in the NSR permit.

Permit Shield. A permit may or may not have a permit shield, depending on whether an applicant has applied for, and justified the granting of, a permit shield. A permit shield is a special condition included in the permit document stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirement(s) or specified applicable state-only requirement(s).

New Source Review Authorization References. All activities which are related to emissions in the state of Texas must have a NSR authorization prior to beginning construction. This section lists all units in the permit and the NSR authorization that allowed the unit to be constructed or modified. Units that do not have unit specific applicable requirements other than the NSR authorization do not need to be listed in this attachment. While NSR permits are not physically a part of the Title V permit, they are legally incorporated into the Title V permit by reference. Those NSR permits whose emissions exceed certain PSD/NA thresholds must also undergo a Federal review of federally regulated pollutants in addition to review for state regulated pollutants.

Compliance Plan. A permit may have a compliance schedule attachment for listing corrective actions plans for any emission unit that is out of compliance with an applicable requirement.

Alternative Requirements. This attachment will list any alternative monitoring plans or alternative means of compliance for applicable requirements that have been approved by the EPA Administrator and/or the TCEQ Executive Director.

Appendix A

Acronym list. This attachment lists the common acronyms used when discussing the FOPs.

Appendix B

Copies of major NSR authorizations applicable to the units covered by this permit have been included in this Appendix, to ensure that all interested persons can access those authorizations.

Stationary vents subject to 30 TAC Chapter 111, Subchapter A, § 111.111(a)(1)(B) addressed in the Special Terms and Conditions

The site contains stationary vents with a flowrate less than 100,000 actual cubic feet per minute (acfm) and constructed either before or after January 31, 1972 which are limited, over a six-minute average, to 20% opacity

as required by 30 TAC § 111.111(a)(1)(B). As a site may have a large number of stationary vents that fall into this category, they are not required to be listed individually in the permit's Applicable Requirement Summary. This is consistent with EPA's White Paper for Streamlined Development of Part 70 Permit Applications, July 10, 1995, that states that requirements that apply identically to emission units at a site can be treated on a generic basis such as source-wide opacity limits.

Periodic monitoring is specified in Special Term and Condition 3 for stationary vents subject to 30 TAC § 111.111(a)(1)(B) to verify compliance with the 20% opacity limit. These vents are not expected to produce visible emissions during normal operation. The TCEQ evaluated the probability of these sources violating the opacity standards and determined that there is a very low potential that an opacity standard would be exceeded. It was determined that continuous monitoring for these sources is not warranted as there would be very limited environmental benefit in continuously monitoring sources that have a low potential to produce visible emissions. Therefore, the TCEQ set the visible observation monitoring frequency for these sources to once per calendar quarter.

The TCEQ has exempted vents that are not capable of producing visible emissions from periodic monitoring requirements. These vents include sources of colorless VOCs, non-fuming liquids, and other materials that cannot produce emissions that obstruct the transmission of light. Passive ventilation vents, such as plumbing vents, are also included in this category. Since this category of vents are not capable of producing opacity due to the physical or chemical characteristics of the emission source, periodic monitoring is not required as it would not yield any additional data to assure compliance with the 20% opacity standard of 30 TAC § 111.111(a)(1)(B).

In the event that visible emissions are detected, either through the quarterly observation or other credible evidence, such as observations from company personnel, the permit holder shall either report a deviation or perform a Test Method 9 observation to determine the opacity consistent with the 6-minute averaging time specified in 30 TAC § 111.111(a)(1)(B). An additional provision is included to monitor combustion sources more frequently than quarterly if alternate fuels are burned for periods greater than 24 consecutive hours. This will address possible emissions that may arise when switching fuel types.

Federal Regulatory Applicability Determinations

The following chart summarizes the applicability of the principal air pollution regulatory programs to the permit area:

Regulatory Program	Applicability (Yes/No)
Prevention of Significant Deterioration (PSD)	Yes
Nonattainment New Source Review (NNSR)	No
Minor NSR	Yes
40 CFR Part 60 - New Source Performance Standards	No
40 CFR Part 61 - National Emission Standards for Hazardous Air Pollutants (NESHAPs)	Yes
40 CFR Part 63 - NESHAPs for Source Categories	Yes
Title IV (Acid Rain) of the Clean Air Act (CAA)	No
Title V (Federal Operating Permits) of the CAA	Yes
Title VI (Stratospheric Ozone Protection) of the CAA	No
CAIR (Clean Air Interstate Rule)	No

Basis for Applying Permit Shields

An operating permit applicant has the opportunity to specifically request a permit shield to document that specific applicable requirements do not apply to emission units in the permit. A permit shield is a special condition stating that compliance with the conditions of the permit shall be deemed compliance with the specified potentially applicable requirements or specified potentially applicable state-only requirements. A permit shield has been requested in the application for specific emission units. For the permit shield requests that have been approved, the basis of determination for regulations that the owner/operator need not comply with are located in the "Permit Shield" attachment of the permit.

Insignificant Activities

In general, units not meeting the criteria for inclusion on either Form OP-SUM or Form OP-REQ1 are not required to be addressed in the operating permit application. Examples of these types of units include, but are not limited to, the following:

1. Office activities such as photocopying, blueprint copying, and photographic processes.
2. Sanitary sewage collection and treatment facilities other than those used to incinerate wastewater treatment plant sludge. Stacks or vents for sanitary sewer plumbing traps are also included.
3. Food preparation facilities including, but not limited to, restaurants and cafeterias used for preparing food or beverages primarily for consumption on the premises.
4. Outdoor barbecue pits, campfires, and fireplaces.
5. Laundry dryers, extractors, and tumblers processing bedding, clothing, or other fabric items generated primarily at the premises. This does not include emissions from dry cleaning systems using perchloroethylene or petroleum solvents.
6. Facilities storing only dry, sweet natural gas, including natural gas pressure regulator vents.
7. Any air separation or other industrial gas production, storage, or packaging facility. Industrial gases, for purposes of this list, include only oxygen, nitrogen, helium, neon, argon, krypton, and xenon.

8. Storage and handling of sealed portable containers, cylinders, or sealed drums.
9. Vehicle exhaust from maintenance or repair shops.
10. Storage and use of non-VOC products or equipment for maintaining motor vehicles operated at the site (including but not limited to, antifreeze and fuel additives).
11. Air contaminant detectors and recorders, combustion controllers and shut-off devices, product analyzers, laboratory analyzers, continuous emissions monitors, other analyzers and monitors, and emissions associated with sampling activities. Exception to this category includes sampling activities that are deemed fugitive emissions and under a regulatory leak detection and repair program.
12. Bench scale laboratory equipment and laboratory equipment used exclusively for chemical and physical analysis, including but not limited to, assorted vacuum producing devices and laboratory fume hoods.
13. Steam vents, steam leaks, and steam safety relief valves, provided the steam (or boiler feedwater) has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
14. Storage of water that has not contacted other materials or fluids containing regulated air pollutants other than boiler water treatment chemicals.
15. Well cellars.
16. Fire or emergency response equipment and training, including but not limited to, use of fire control equipment including equipment testing and training, and open burning of materials or fuels associated with firefighting training.
17. Crucible or pot furnaces with a brim full capacity of less than 450 cubic inches of any molten metal.
18. Equipment used exclusively for the melting or application of wax.
19. All closed tumblers used for the cleaning or deburring of metal products without abrasive blasting, and all open tumblers with a batch capacity of 1,000 lbs. or less.
20. Shell core and shell mold manufacturing machines.
21. Sand or investment molds with a capacity of 100 lbs. or less used for the casting of metals;
22. Equipment used for inspection of metal products.
23. Equipment used exclusively for rolling, forging, pressing, drawing, spinning, or extruding either hot or cold metals by some mechanical means.
24. Instrument systems utilizing air, natural gas, nitrogen, oxygen, carbon dioxide, helium, neon, argon, krypton, and xenon.
25. Battery recharging areas.
26. Brazing, soldering, or welding equipment.

Determination of Applicable Requirements

The tables below include the applicability determinations for the emission units, the index number(s) where applicable, and all relevant unit attribute information used to form the basis of the applicability determination. The unit attribute information is a description of the physical properties of an emission unit which is used to determine the requirements to which the permit holder must comply. For more information about the descriptions of the unit attributes specific Unit Attribute Forms may be viewed at www.tceq.texas.gov/permitting/air/nav/air_all_ua_forms.html.

A list of unit attribute forms is included at the end of this document. Some examples of unit attributes include construction date; product stored in a tank; boiler fuel type; etc.. Generally, multiple attributes are needed to determine the requirements for a given emission unit and index number. The table below lists these attributes in the column entitled "Basis of Determination." Attributes that demonstrate that an applicable requirement applies will be the factual basis for the specific citations in an applicable requirement that apply to a unit for that index number. The TCEQ Air Permits Division has developed flowcharts for determining applicability of state and federal regulations based on the unit attribute information in a Decision Support System (DSS). These flowcharts can be accessed via the internet at www.tceq.texas.gov/permitting/air/nav/air_supportsys.html. The Air Permits Division staff may also be contacted for assistance at (512) 239-1250.

The attributes for each unit and corresponding index number provide the basis for determining the specific legal citations in an applicable requirement that apply, including emission limitations or standards, monitoring, recordkeeping, and reporting. The rules were found to apply or not apply by using the unit attributes as answers to decision questions found in the flowcharts of the DSS. Some additional attributes indicate which legal citations of a rule apply. The legal citations that apply to each emission unit may be found in the Applicable Requirements Summary table of the draft permit. There may be some entries or rows of units and rules not found in the permit, or if the permit contains a permit shield, repeated in the permit shield area. These are sets of attributes that describe negative applicability, or; in other words, the reason why a potentially applicable requirement does not apply.

If applicability determinations have been made which differ from the available flowcharts, an explanation of the decisions involved in the applicability determination is specified in the column “Changes and Exceptions to RRT.” If there were no exceptions to the DSS, then this column has been removed.

The draft permit includes all emission limitations or standards, monitoring, recordkeeping and reporting required by each applicable requirement. If an applicable requirement does not require monitoring, recordkeeping, or reporting, the word “None” will appear in the Applicable Requirements Summary table. If additional periodic monitoring is required for an applicable requirement, it will be explained in detail in the portion of this document entitled “Rationale for Compliance Assurance Monitoring (CAM)/ Periodic Monitoring Methods Selected.”

When attributes demonstrate that a unit is not subject to an applicable requirement, the applicant may request a permit shield for those items. The portion of this document entitled “Basis for Applying Permit Shields” specifies which units, if any, have a permit shield.

Operational Flexibility

When an emission unit has multiple operating scenarios, it will have a different index number associated with each operating condition. This means that units are permitted to operate under multiple operating conditions. The applicable requirements for each operating condition are determined by a unique set of unit attributes. For example, a tank may store two different products at different points in time. The tank may, therefore, need to comply with two distinct sets of requirements, depending on the product that is stored. Both sets of requirements are included in the permit, so that the permit holder may store either product in the tank.

Determination of Applicable Requirements

Unit ID	Regulation	Index Number	Basis of Determination*
EPO21T47	40 CFR Part 63, Subpart EEEE	63EEEE-0001	Product Stored = Organic HAP containing liquid other than crude oil.
EPO21T48	40 CFR Part 63, Subpart EEEE	63EEEE-0001	Product Stored = Organic HAP containing liquid other than crude oil.
OL266T1001	40 CFR Part 63, Subpart FFFF	63FFFF-0010	Designated HAL = The emission stream is not designated as halogenated. Emission Standard = HAP vapor pressure is less than 76.6 and a flare is being used for control per § 63.2470(a)-Table 4.1.b.iii. Determined HAL = The emission stream is determined not to be halogenated. Prior Eval = The data from a prior evaluation or assessment is used. Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure. Bypass Line = The closed vent system does not contain a bypass line that could divert the vent stream away from the control device.
SDO20T111	40 CFR Part 63, Subpart FFFF	63FFFF-0001	Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i. WW Tank Control = An internal floating roof is operated and maintained per 40 CFR § 63.1062(a)(1). Notification = The referencing subpart requires notification of initial startup. Unslotted Guide Pole = The tank uses an unslotted guide pole. Wiper or Seal = The unslotted guide pole is equipped with a pole wiper and a pole sleeve. Seal Configuration = Two seals mounted one above the other. Inspection Requirement = Complying with the inspection requirement in §63.1063(c)(1)(i).
SDO20T118	40 CFR Part 63, Subpart FFFF	63FFFF-0001	Emission Standard = HAP vapor pressure is < 76.6 and the unit is complying with 40 CFR Part 63, subpart WW per § 63.2470(a)-Table 4.1.b.i. WW Tank Control = An internal floating roof is operated and maintained per 40 CFR § 63.1062(a)(1). Notification = The referencing subpart requires notification of initial startup. Unslotted Guide Pole = The tank uses an unslotted guide pole. Wiper or Seal = The unslotted guide pole is equipped with a pole wiper and a pole sleeve. Seal Configuration = Two seals mounted one above the other. Inspection Requirement = Complying with the inspection requirement in §63.1063(c)(1)(i).
SDO21T133	40 CFR Part 63, Subpart EEEE	63EEEE-0001	Product Stored = Organic HAP containing liquid other than crude oil.
SDO52T2	40 CFR Part 61, Subpart FF	61FF-0001	Tank Control Requirements = The waste managed in the tank meets the conditions in 40 CFR § 61.343(b)(1) and the tank is complying with the requirements specified in 40 CFR § 61.343(b)(2). Waste Treatment Tank = The tank manages, treats or stores a waste stream subject to 40 CFR Part 61, Subpart FF. Alternative Standard for Tanks = The tank is not complying with the alternative standards in 40 CFR § 61.351. Fuel Gas System = Gaseous emissions from the tank or enclosure are not routed to a fuel gas system. Closed Vent System and Control Device = No closed vent system and control device is used. Alternative Means of Compliance = Not using an alternate means of compliance to meet the requirements of 40 CFR § 61.343 for tanks.
SDO04LR1	40 CFR Part 63,	63G-0001	Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other

Unit ID	Regulation	Index Number	Basis of Determination*
	Subpart G		<p>than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system or is subject to § 63.148 of Subpart G.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>
SD004LT41	40 CFR Part 63, Subpart G	63G-0001	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system or is subject to § 63.148 of Subpart G.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>
SD008LR1	40 CFR Part 63, Subpart G	63G-0002	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>
SD008LR1	40 CFR Part 63, Subpart YY	63YY-0007	<p>Source Type = Ethylene production.</p> <p>Average Volume Transferred = Volume transferred is less than 76 m³ per day (20,077 gallons per day), averaged over any 30 consecutive days.</p>
SD020LT53	40 CFR Part 63, Subpart G	63G-0002	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>
SD022LT50	40 CFR Part 61, Subpart BB	61BB-0001	<p>Negative Applicability = The loading rack loads materials other than benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.</p> <p>Benzene By Weight = Concentration of benzene by weight in the liquid which is loaded is less than 70% benzene by weight.</p> <p>Annual Amount Loaded = Annual amount loaded is less than 1.3 million liters (343,424 gallons).</p>
SD022LT50	40 CFR Part 63, Subpart YY	63YY-0007	<p>Source Type = Ethylene production.</p> <p>True Vapor Pressure = The true vapor pressure of the loaded material is at least 3.4 kPa (0.5 psi).</p> <p>Average Volume Transferred = Volume transferred is at least 76 m³ per day (20,077 gallons per day), averaged over any 30 consecutive days.</p>
SD022LT51	40 CFR Part 63, Subpart G	63G-0002	<p>Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
SD022LT52	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD036LR1	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD036LT93	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD052LT6	40 CFR Part 61, Subpart BB	61BB-0001	Negative Applicability = The loading rack loads only benzene-laden waste, gasoline, crude oil, natural gas liquids, petroleum distillates or benzene-laden liquid from a coke by-product plant.
SD093LR1	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD098LT90	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD101LR1	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD101LT92	40 CFR Part 63, Subpart G	63G-0002	Transfer Rack Type = Group 2 transfer rack (as defined in 40 CFR § 63.111). Subject to Subpart BB = The transfer rack is not subject to 40 CFR Part 61, Subpart BB.
SD103LR1	40 CFR Part 63, Subpart G	63G-0001	Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b). Control Device = Flare. Halogenated Emissions = There are no halogenated emission streams from the transfer rack. Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111). Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants. Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv). Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device. Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system or is subject to § 63.148 of Subpart G. Hard Piping = The closed vent system is constructed of hard piping.
SD103LR1	40 CFR Part 63, Subpart G	63G-0003	Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111). Vapor Balancing System = A vapor balancing system is being used to reduce emissions of organic hazardous air pollutants. Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device. Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system or is subject to § 63.148 of Subpart G. Hard Piping = The closed vent system is constructed of hard piping.
SD103LR1	40 CFR Part 63, Subpart YY	63YY-0005	Source Type = Ethylene production. True Vapor Pressure = The true vapor pressure of the loaded material is at least 3.4 kPa (0.5 psi). Average Volume Transferred = Volume transferred is at least 76 m ³ per day (20,077 gallons per day), averaged over any 30 consecutive days.

Unit ID	Regulation	Index Number	Basis of Determination*
SD103LT20	40 CFR Part 63, Subpart G	63G-0001	<p>Alternate Parameter Monitoring = Approval has not been sought or has not been granted by the EPA Administrator to monitor a parameter other than those specified in 40 CFR § 63.127(a) - (b).</p> <p>Control Device = Flare.</p> <p>Halogenated Emissions = There are no halogenated emission streams from the transfer rack.</p> <p>Transfer Rack Type = Group 1 transfer rack (as defined in 40 CFR § 63.111).</p> <p>Vapor Balancing System = A vapor balancing system is not being used to reduce emissions of organic hazardous air pollutants.</p> <p>Emissions Routing = Emissions of organic hazardous air pollutants are not routed to a fuel gas system nor to a process where the organic hazardous air pollutants meet one or more of the ends specified in 40 CFR § 63.126(b)(4)(i) - (iv).</p> <p>Bypass Lines = The vent system does not contain by-pass lines that could divert a vent stream flow away from the control device.</p> <p>Closed Vent System = Closed vent system is routing emissions to a process or fuel gas system or is subject to § 63.148 of Subpart G.</p> <p>Hard Piping = The closed vent system is constructed of hard piping.</p>
SD103LT20	40 CFR Part 63, Subpart YY	63YY-0005	<p>Source Type = Ethylene production.</p> <p>True Vapor Pressure = The true vapor pressure of the loaded material is at least 3.4 kPa (0.5 psi).</p> <p>Average Volume Transferred = Volume transferred is at least 76 m³ per day (20,077 gallons per day), averaged over any 30 consecutive days.</p>
SD225LT110	40 CFR Part 63, Subpart YY	63YY-0008	<p>Source Type = Ethylene production.</p> <p>True Vapor Pressure = The true vapor pressure of the loaded material is less than 3.4 kPa (0.5 psi).</p> <p>Average Volume Transferred = Volume transferred is less than 76 m³ per day (20,077 gallons per day), averaged over any 30 consecutive days.</p>
SD236LR1	40 CFR Part 63, Subpart FFFF	63FFFF-0011	<p>Emission Standard = A flare is being used per § 63.2475(a) - Table 5.1.b.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be nonhalogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is used.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = The CVS does not contain any bypass line that could divert the vent stream away from the control device.</p>
SD236LR1	40 CFR Part 63, Subpart YY	63YY-0005	<p>Source Type = Ethylene production.</p> <p>True Vapor Pressure = The true vapor pressure of the loaded material is at least 3.4 kPa (0.5 psi).</p> <p>Average Volume Transferred = Volume transferred is at least 76 m³ per day (20,077 gallons per day), averaged over any 30 consecutive days.</p>
SD236LT120	40 CFR Part 63, Subpart FFFF	63FFFF-0011	<p>Emission Standard = A flare is being used per § 63.2475(a) - Table 5.1.b.</p> <p>Designated Hal = The emission stream is not designated as halogenated.</p> <p>Determined Hal = The emission stream is determined to be nonhalogenated.</p> <p>Prior Eval = The data from a prior evaluation or assessment is used.</p> <p>Negative Pressure = The closed vent system is operated and maintained at or above atmospheric pressure.</p> <p>Bypass Line = The CVS does not contain any bypass line that could divert the vent stream away from the control device.</p>
SD236LT120	40 CFR Part 63, Subpart YY	63YY-0005	<p>Source Type = Ethylene production.</p> <p>True Vapor Pressure = The true vapor pressure of the loaded material is at least 3.4 kPa (0.5 psi).</p> <p>Average Volume Transferred = Volume transferred is at least 76 m³ per day (20,077 gallons per day), averaged over any 30 consecutive days.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
SD052FL1	30 TAC Chapter 111, Visible Emissions	R1111-0003	Acid Gases Only = Flare is not used only as an acid gas flare as defined in 30 TAC § 101.1. Emergency/Upset Conditions Only = Flare is used under conditions other than emergency or upset conditions.
SD052FL1	40 CFR Part 63, Subpart A	63A-0003	Required Under 40 CFR Part 63 = Flare is required by a Subpart under 40 CFR Part 63. Heat Content Specification = Adhering to the heat content specifications in 40 CFR § 63.11(b)(6)(ii) and the maximum tip velocity specifications in 40 CFR § 63.11(b)(7) or 40 CFR § 63.11(b)(8). Flare Assist Type = Non-assisted Flare Exit Velocity = Flare exit velocity is less than 60 ft/s (18.3 m/sec)
SD004FGL	40 CFR Part 63, Subpart H	63H-0001	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			LIMITATION (AMEL) FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177 HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.
SD008FGL	40 CFR Part 63, Subpart FFFF	63FFFF-0002	Existing Source = Fugitive unit contains equipment in an existing Miscellaneous Chemical Processing Unit.
SD008FGL	40 CFR Part 63, Subpart H	63H-0002	ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179 EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178 GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE ANY (COMPRESSORS) = COMPONENT NOT PRESENT EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.</p>
SD008FGL	40 CFR Part 63, Subpart YY	63YY-0002	<p>Source Type = Ethylene Production.</p> <p>Equipment Type = The fugitive unit contains equipment, as defined in § 63.1101, contactin hazardous air pollutants in Tables 1 through 7 or Table 9, as appropriate.</p>
SD020FG1	40 CFR Part 63, Subpart FFFF	63FFFF-0002	Existing Source = Fugitive unit contains equipment in an existing Miscellaneous Chemical Processing Unit.
SD036FGL	40 CFR Part 63, Subpart H	63H-0004	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.</p>
SD052FG2	40 CFR Part 61, Subpart J	61J-0001	<p>40 CFR 61 (NESHAP) SUBPART J DESIGN CAPACITY = SITE IS DESIGNED TO PRODUCE OR USE MORE THAN 1,000 MEGAGRAMS OF BENZENE PER YEAR</p> <p>ANY COMPONENT IN BENZENE SERVICE [NESHAP J] = THE FACILITY CONTAINS ANY COMPONENT(S) IN BENZENE SERVICE</p> <p>40 CFR 61 (NESHAP) SUBPART J ALTERNATE MEANS OF EMISSION LIMITATION (AMEL) = NOT USING ALTERNATE MEANS OF EMISSION LIMITATION.</p>
SD052FG2	40 CFR Part 61, Subpart V	61V-0001	<p>Compressors = The fugitive unit does not contain compressors in VHAP service.</p> <p>Enclosed Combustion Device = The fugitive unit does not contain enclosed combustion devices in VHAP service.</p> <p>Flare = The fugitive unit does not contain flares.</p> <p>Pressure Relief Devices in Gas/Vapor Service = The fugitive unit does not contain pressure relief devices in gas/vapor VHAP service.</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>Product Accumulator Vessels = The fugitive unit does not contain product accumulator vessels.</p> <p>Sampling Connection Systems = The fugitive unit does not contain sampling connection systems in VHAP service.</p> <p>Vacuum Service = The fugitive unit does not contain components in vacuum service.</p> <p>Valves = The fugitive unit contains valves in VHAP service.</p> <p>Vapor Recovery System = The fugitive unit does not contain vapor recovery systems in VHAP service.</p> <p>AMEL = No alternate method of emission limitation is used for valves.</p> <p>VHAP Service = The fugitive unit contains components in VHAP service.</p> <p>Pumps = The fugitive unit does not contain pumps in VHAP service.</p> <p>Complying with 40 CFR § 61.242-7 = Valves are complying with § 61.242-7.</p> <p>Flanges and Other Connectors = The fugitive unit contains flanges and other connectors in VHAP service.</p> <p>Open-ended Valves or Lines = The fugitive unit contains open-ended valves or lines in VHAP service.</p> <p>Pressure Relief Devices in Liquid Service = The fugitive unit does not contain pressure relief devices in liquid VHAP service.</p> <p>AMEL = No alternate method of emission limitation is used for open-ended valves or lines.</p> <p>Complying with 40 CFR § 61.242-6 = Open-ended valves or lines are complying with § 61.242-6.</p> <p>Complying with 40 CFR § 61.242-8 = Flanges and other connectors are complying with § 61.242-8.</p>
SD093FGL	40 CFR Part 63, Subpart H	63H-0005	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.</p>
SD101FGL	40 CFR Part 63, Subpart H	63H-0006	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.</p>
SD103FGL	40 CFR Part 63, Subpart FFFF	63FFFF-0002	Existing Source = Fugitive unit contains equipment in an existing Miscellaneous Chemical Processing Unit.
SD103FGL	40 CFR Part 63, Subpart H	63H-0003	<p>ANY (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (OPEN-ENDED VALVES OR LINES) = COMPONENT PRESENT</p> <p>ENCLOSED-VENTED PROCESS UNIT AMEL = UNIT DOES NOT CONTAIN A TOTALLY ENCLOSED VENTED PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.179</p> <p>EQUIPMENT TYPE = FUGITIVE UNIT CONTAINS EQUIPMENT LISTED IN 40 CFR § 63.160(A) WHICH IS OPERATED IN ORGANIC HAZARDOUS AIR POLLUTANT SERVICE</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>LIGHT LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (AGITATORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (OPEN-ENDED VALVES OR LINES) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PUMPS) = COMPONENT NOT PRESENT</p> <p>NON RESEARCH AND DEVELOPMENT/BATCH PROCESSES = FUGITIVE UNIT CONTAINS PROCESSES OTHER THAN RESEARCH AND</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			<p>DEVELOPMENT FACILITIES AND BENCH-SCALE BATCH PROCESSES</p> <p>RECOVERY OR RECAPTURE DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>ANY (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>BATCH PROCESS AMEL = UNIT DOES NOT CONTAIN A BATCH PROCESS UNIT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION IN § 63.178</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (VALVES) = COMPONENT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR PUMPS</p> <p>VACUUM SERVICE = NOT ALL OF THE EQUIPMENT IN THE FUGITIVE UNIT IS IN VACUUM SERVICE</p> <p>ANY (COMPRESSORS) = COMPONENT NOT PRESENT</p> <p>EMPLOYEE NUMBER = THE CORPORATION EMPLOYS 100 OR MORE PERSONS</p> <p>ENCLOSED COMBUSTION DEVICES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (INSTRUMENTATION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (VALVES) = COMPONENT NOT PRESENT</p> <p>LESS THAN 300 OPERATING HOURS = THE FUGITIVE UNIT DOES NOT CONTAIN ANY EQUIPMENT IN ORGANIC HAZARDOUS AIR POLLUTANT (HAP) SERVICE THAT IS INTENDED TO OPERATE LESS THAN 300 HOURS PER CALENDAR YEAR</p> <p>ANY (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>GAS VAPOR SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>QIP = UNIT DOES NOT OPT TO COMPLY WITH A QUALITY IMPROVEMENT PROGRAM FOR VALVES</p> <p>AMEL = FUGITIVE UNIT SOURCE OWNER/OPERATOR IS NOT ELECTING TO COMPLY WITH AN ALTERNATIVE MEANS OF EMISSION LIMITATION (AMEL)</p> <p>FLARES (CLOSED VENT SYSTEMS) = COMPONENT NOT PRESENT</p> <p>GAS/VAPOR OR LIGHT LIQUID SERVICE (CONNECTORS) = COMPONENT PRESENT</p> <p>GENERAL AMEL = UNIT IS NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION UNDER § 63.177</p> <p>HEAVY LIQUID SERVICE (SURGE CONTROL VESSELS OR BOTTOMS RECEIVERS) = COMPONENT NOT PRESENT</p> <p>LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (CONNECTORS) = COMPONENT NOT PRESENT</p> <p>HEAVY LIQUID SERVICE (PRESSURE RELIEF DEVICES) = COMPONENT NOT PRESENT</p> <p>ANY (SAMPLING CONNECTION SYSTEMS) = COMPONENT PRESENT</p> <p>HEAVY LIQUID SERVICE (SAMPLING CONNECTION SYSTEMS) = COMPONENT NOT PRESENT</p> <p>UNITS WITHOUT AMEL = FUGITIVE UNIT EQUIPMENT OR PROCESS UNITS ARE NOT COMPLYING WITH AN ALTERNATE MEANS OF EMISSION LIMITATION.</p>
SD103FGL	40 CFR Part 63, Subpart YY	63YY-0002	<p>Source Type = Ethylene Production.</p> <p>Equipment Type = The fugitive unit contains equipment, as defined in § 63.1101, contactin hazardous air pollutants in Tables 1 through 7 or Table 9, as appropriate.</p>
SD106FGL	40 CFR Part 63, Subpart FFFF	63FFFF-0002	<p>Existing Source = Fugitive unit contains equipment in an existing Miscellaneous Chemical Processing Unit.</p>
SD225FGL	40 CFR Part 63, Subpart YY	63YY-0002	<p>Source Type = Ethylene Production.</p> <p>Equipment Type = The fugitive unit contains equipment, as defined in § 63.1101, contactin hazardous air pollutants in Tables 1 through 7 or Table</p>

Unit ID	Regulation	Index Number	Basis of Determination*
			9, as appropriate.
SD236FGL	40 CFR Part 63, Subpart FFFF	63FFFF-0002	Existing Source = Fugitive unit contains equipment in an existing Miscellaneous Chemical Processing Unit.
SD236FGL	40 CFR Part 63, Subpart YY	63YY-0002	Source Type = Ethylene Production. Equipment Type = The fugitive unit contains equipment, as defined in § 63.1101, contactin hazardous air pollutants in Tables 1 through 7 or Table 9, as appropriate.

* - The "unit attributes" or operating conditions that determine what requirements apply

NSR versus Title V FOP

The state of Texas has two Air permitting programs, New Source Review (NSR) and Title V Federal Operating Permits. The two programs are substantially different both in intent and permit content.

NSR is a preconstruction permitting program authorized by the Texas Clean Air Act and Title I of the Federal Clean Air Act (FCAA). The processing of these permits is governed by 30 Texas Administrative Code (TAC) Chapter 116.111. The Title V Federal Operating Program is a federal program authorized under Title V of the FCAA that has been delegated to the state of Texas to administer and is governed by 30 TAC Chapter 122. The major differences between the two permitting programs are listed in the table below:

NSR Permit	Federal Operating Permit(FOP)
Issued Prior to new Construction or modification of an existing facility	For initial permit with application shield, can be issued after operation commences; significant revisions require approval prior to operation.
Authorizes air emissions	Codifies existing applicable requirements, does not authorize new emissions
Ensures issued permits are protective of the environment and human health by conducting a health effects review and that requirement for best available control technology (BACT) is implemented.	Applicable requirements listed in permit are used by the inspectors to ensure proper operation of the site as authorized. Ensures that adequate monitoring is in place to allow compliance determination with the FOP.
Up to two Public notices may be required. Opportunity for public comment and contested case hearings for some authorizations.	One public notice required. Opportunity for public comments. No contested case hearings.
Applies to all point source emissions in the state.	Applies to all major sources and some non-major sources identified by the EPA.
Applies to facilities: a portion of site or individual emission sources	One or multiple FOPs cover the entire site (consists of multiple facilities)
Permits include terms and conditions under which the applicant must construct and operate its various equipment and processes on a facility basis.	Permits include terms and conditions that specify the general operational requirements of the site; and also include codification of all applicable requirements for emission units at the site.
Opportunity for EPA review for Federal Prevention of Significant Deterioration (PSD) and Nonattainment (NA) permits for major sources.	Opportunity for EPA review, Affected states review, and a Public petition period for every FOP.
Permits have a table listing maximum emission limits for pollutants	Permit has an applicable requirements table and Periodic Monitoring (PM) / Compliance Assurance Monitoring (CAM) tables which document applicable monitoring requirements.
Permits can be altered or amended upon application by company. Permits must be issued before construction or modification of facilities can begin.	Permits can be revised through several revision processes, which provide for different levels of public notice and opportunity to comment. Changes that would be significant revisions require that a revised permit be issued before those changes can be operated.
NSR permits are issued independent of FOP requirements.	FOP are independent of NSR permits, but contain a list of all NSR permits incorporated by reference

New Source Review Requirements

Below is a list of the New Source Review (NSR) permits for the permitted area. These NSR permits are incorporated by reference into the operating permit and are enforceable under it. These permits can be found in the main TCEQ file room, located on the first floor of Building E, 12100 Park 35 Circle, Austin, Texas. The

Public Education Program may be contacted at 1-800-687-4040 or the Air Permits Division (APD) may be contacted at 1-512-239-1250 for help with any question.

Additionally, the site contains emission units that are permitted by rule under the requirements of 30 TAC Chapter 106, Permits by Rule. The following table specifies the permits by rule that apply to the site. All current permits by rule are contained in Chapter 106. Outdated 30 TAC Chapter 106 permits by rule may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/old106list/index106.html

Outdated Standard Exemption lists may be viewed at the following Web site:

www.tceq.texas.gov/permitting/air/permitbyrule/historical_rules/oldselist/se_index.html

Prevention of Significant Deterioration (PSD) Permits	
PSD Permit No.: PSDTX332M3	Issuance Date: 12/10/2013
Title 30 TAC Chapter 116 Permits, Special Permits, and Other Authorizations (Other Than Permits By Rule, PSD Permits, or NA Permits) for the Application Area.	
Authorization No.: 1105	Issuance Date: 02/17/2012
Authorization No.: 1329	Issuance Date: 05/21/2007
Authorization No.: 17578	Issuance Date: 09/27/2004
Authorization No.: 18528	Issuance Date: 02/29/2012
Authorization No.: 21832	Issuance Date: 02/12/2013
Authorization No.: 27941	Issuance Date: 06/02/2006
Authorization No.: 48591	Issuance Date: 10/16/2013
Authorization No.: 48615	Issuance Date: 03/29/2005
Authorization No.: 48617	Issuance Date: 04/24/2013
Authorization No.: 48626	Issuance Date: 06/08/2012
Authorization No.: 48655	Issuance Date: 06/04/2013
Authorization No.: 48758	Issuance Date: 09/06/2011
Authorization No.: 48761	Issuance Date: 01/23/2015
Authorization No.: 49363	Issuance Date: 09/04/2004
Authorization No.: 52985	Issuance Date: 11/10/2005
Authorization No.: 6419	Issuance Date: 11/13/2006
Authorization No.: 6777	Issuance Date: 10/11/2006
Authorization No.: 78809	Issuance Date: 03/20/2012
Authorization No.: 84724	Issuance Date: 08/19/2013
Authorization No.: 85136	Issuance Date: 06/16/2008
Authorization No.: 8539	Issuance Date: 12/10/2013

Authorization No.: 9552	Issuance Date: 10/03/2012
Authorization No.: 9631	Issuance Date: 06/12/2014
Permits By Rule (30 TAC Chapter 106) for the Application Area	
Number: 106.122	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 03/14/1997
Number: 106.261	Version No./Date: 09/04/2000
Number: 106.261	Version No./Date: 11/01/2003
Number: 106.262	Version No./Date: 12/24/1998
Number: 106.262	Version No./Date: 09/04/2000
Number: 106.262	Version No./Date: 11/01/2003
Number: 106.263	Version No./Date: 11/01/2001
Number: 106.472	Version No./Date: 03/14/1997
Number: 106.472	Version No./Date: 09/04/2000
Number: 106.473	Version No./Date: 09/04/2000
Number: 106.478	Version No./Date: 03/14/1997
Number: 106.478	Version No./Date: 09/04/2000

Emission Units and Emission Points

In air permitting terminology, any source capable of generating emissions (for example, an engine or a sandblasting area) is called an Emission Unit. For purposes of Title V, emission units are specifically listed in the operating permit when they have applicable requirements other than New Source Review (NSR), or when they are listed in the permit shield table.

The actual physical location where the emissions enter the atmosphere (for example, an engine stack or a sandblasting yard) is called an emission point. For New Source Review preconstruction permitting purposes, every emission unit has an associated emission point. Emission limits are listed in an NSR permit, associated with an emission point. This list of emission points and emission limits per pollutant is commonly referred to as the “Maximum Allowable Emission Rate Table”, or “MAERT” for short. Specifically, the MAERT lists the Emission Point Number (EPN) that identifies the emission point, followed immediately by the Source Name, identifying the emission unit that is the source of those emissions on this table.

Thus, by reference, an emission unit in a Title V operating permit is linked by reference number to an NSR authorization, and its related emission point.

Monitoring Sufficiency

Federal and state rules, 40 CFR § 70.6(a)(3)(i)(B) and 30 TAC § 122.142(c) respectively, require that each federal operating permit include additional monitoring for applicable requirements that lack periodic or instrumental monitoring (which may include recordkeeping that serves as monitoring) that yields reliable data from a relevant time period that are representative of the emission unit’s compliance with the applicable emission limitation or standard. Furthermore, the federal operating permit must include compliance assurance monitoring (CAM) requirements for emission sources that meet the applicability criteria of 40 CFR Part 64 in accordance with 40 CFR § 70.6(a)(3)(i)(A) and 30 TAC § 122.604(b).

With the exception of any emission units listed in the Periodic Monitoring or CAM Summaries in the FOP, the TCEQ Executive Director has determined that the permit contains sufficient monitoring, testing, recordkeeping, and reporting requirements that assure compliance with the applicable requirements. If applicable, each emission unit that requires additional monitoring in the form of periodic monitoring or CAM is described in further detail under the Rationale for CAM/PM Methods Selected section following this paragraph.

Compliance Review

1. In accordance with 30 TAC Chapter 60, the compliance history was reviewed on 12/05/2014.
2. The compliance history review evaluated the period from 04/27/2014 to 04/27/2014.
 Site rating: 0.00 Company rating: 0.00
 (*High < 0.10; Satisfactory > 0.10 and < 55; Unsatisfactory > 55*)
3. Has the permit changed on the basis of the compliance history or site/company rating?No

Site/Permit Area Compliance Status Review

1. Were there any out-of-compliance units listed on Form OP-ACPS?No
2. Is a compliance plan and schedule included in the permit?No

Available Unit Attribute Forms

- OP-UA1 - Miscellaneous and Generic Unit Attributes
- OP-UA2 - Stationary Reciprocating Internal Combustion Engine Attributes
- OP-UA3 - Storage Tank/Vessel Attributes
- OP-UA4 - Loading/Unloading Operations Attributes
- OP-UA5 - Process Heater/Furnace Attributes
- OP-UA6 - Boiler/Steam Generator/Steam Generating Unit Attributes
- OP-UA7 - Flare Attributes
- OP-UA8 - Coal Preparation Plant Attributes
- OP-UA9 - Nonmetallic Mineral Process Plant Attributes
- OP-UA10 - Gas Sweetening/Sulfur Recovery Unit Attributes
- OP-UA11 - Stationary Turbine Attributes
- OP-UA12 - Fugitive Emission Unit Attributes
- OP-UA13 - Industrial Process Cooling Tower Attributes
- OP-UA14 - Water Separator Attributes
- OP-UA15 - Emission Point/Stationary Vent/Distillation Operation/Process Vent Attributes
- OP-UA16 - Solvent Degreasing Machine Attributes
- OP-UA17 - Distillation Unit Attributes
- OP-UA18 - Surface Coating Operations Attributes
- OP-UA19 - Wastewater Unit Attributes
- OP-UA20 - Asphalt Operations Attributes
- OP-UA21 - Grain Elevator Attributes
- OP-UA22 - Printing Attributes
- OP-UA24 - Wool Fiberglass Insulation Manufacturing Plant Attributes
- OP-UA25 - Synthetic Fiber Production Attributes
- OP-UA26 - Electroplating and Anodizing Unit Attributes
- OP-UA27 - Nitric Acid Manufacturing Attributes
- OP-UA28 - Polymer Manufacturing Attributes
- OP-UA29 - Glass Manufacturing Unit Attributes
- OP-UA30 - Kraft, Soda, Sulfite, and Stand-Alone Semicheical Pulp Mill Attributes
- OP-UA31 - Lead Smelting Attributes
- OP-UA32 - Copper and Zinc Smelting/Brass and Bronze Production Attributes
- OP-UA33 - Metallic Mineral Processing Plant Attributes
- OP-UA34 - Pharmaceutical Manufacturing

OP-UA35 - Incinerator Attributes
OP-UA36 - Steel Plant Unit Attributes
OP-UA37 - Basic Oxygen Process Furnace Unit Attributes
OP-UA38 - Lead-Acid Battery Manufacturing Plant Attributes
OP-UA39 - Sterilization Source Attributes
OP-UA40 - Ferroalloy Production Facility Attributes
OP-UA41 - Dry Cleaning Facility Attributes
OP-UA42 - Phosphate Fertilizer Manufacturing Attributes
OP-UA43 - Sulfuric Acid Production Attributes
OP-UA44 - Municipal Solid Waste Landfill/Waste Disposal Site Attributes
OP-UA45 - Surface Impoundment Attributes
OP-UA46 - Epoxy Resins and Non-Nylon Polyamides Production Attributes
OP-UA47 - Ship Building and Ship Repair Unit Attributes
OP-UA48 - Air Oxidation Unit Process Attributes
OP-UA49 - Vacuum-Producing System Attributes
OP-UA50 - Fluid Catalytic Cracking Unit Catalyst Regenerator/Fuel Gas Combustion Device/Claus Sulfur Recovery Plant Attributes
OP-UA51 - Dryer/Kiln/Oven Attributes
OP-UA52 - Closed Vent Systems and Control Devices
OP-UA53 - Beryllium Processing Attributes
OP-UA54 - Mercury Chlor-Alkali Cell Attributes
OP-UA55 - Transfer System Attributes
OP-UA56 - Vinyl Chloride Process Attributes
OP-UA57 - Cleaning/Depainting Operation Attributes
OP-UA58 - Treatment Process Attributes
OP-UA59 - Coke By-Product Recovery Plant Attributes
OP-UA60 - Chemical Manufacturing Process Unit Attributes
OP-UA61 - Pulp, Paper, or Paperboard Producing Process Attributes
OP-UA62 - Glycol Dehydration Unit Attributes
OP-UA63 - Vegetable Oil Production Attributes